

Step 1. Use the Mercenary tuner to flash in the “STOCK” tune:

Flashing the EFI Live “Stock” calibration into the ECM:

Plug Mercenary into your trucks OBDII port with key in the RUN position the tuner will say “Scan tool” Press the next button to see "Tuning Tool" option, Press the OK (middle Button) and then press the next button until you see "Program Full" press the next button until you see a file name that will say “STOCK”. Press the ok button and the tuner will ask "license ECU now?" Press OK button, from there the tuner will load in the “STOCK” file starting at 0% and working up to %100. Once the file has loaded the tuner will display "ignition off now". Turn off the ignition and press ok. The tuner will count down from 10. You can now unplug the tuner and begin the BULLY DOG UNLOCK PROCESS USING THE INSTRUCTIONS THAT CAME WITH THE BULLY DOG. You will select the year 2015 Cummins on the BULLY DOG for the Unlock process.

Step 2. Unlocking your trucks ECM:

Please follow the instructions included with the Bully Dog GT tuner to perform this task.

Step: 3 Flashing the EFI Live Custom Delete Tune (CSP5MOD) into truck

Once you have unlocked your ecm, you are ready to flash in a custom tune file. To do this, once again select the "Tuning Tool" option, with the key in the run position and the engine off, from the main menu. Then, press the next button until you see "Program Full". Next, press the next button until you see a file name that will say CSPMOD. Press the ok button and the tuner will ask "license ECU now?" Select ok (if you unlocked your ecm this step will be skipped), from there the tuner will load in the file starting at 0% and working up to %100. Once the file has loaded the tuner will display "ignition off now". Turn off the ignition and press ok. The tuner will count down from 10. You can now unplug the tuner and start your truck.

Selecting a power level: If you do have a CSP4 switch you may now plug it in and it will work. If you do not have a CSP switch you can still change power levels on the fly using the tuner. From the main menu, press next once and

select "Tuning Tool". Using the Next button scroll down until you see "Switch Tunes" and press ok. Then scroll down until you find the tune you want and press ok. The tuner will now either say "tune switched" or "switch failed". If it says switch failed, unplug the tuner ensure truck is running and then plug it back in. Repeat the steps to change tunes until you see the "tune switched" message.

Step 4. Reading and Clearing DTCs

To read DTCs, plug the tuner into the OBD-II port and turn the ignition to run, using the next button scroll down to "Trouble Codes". Next scroll down to "Display all DTCs". Press select and any DTCs will display one at a time. Use the next button to scroll to the end of the list.

To clear DTCs, scroll down to the "Clear Codes" option. Press the ok button, the tuner will ask you if you are sure select ok and the tuner will then clear the DTCs in the truck. You will hear three chimes from the dash and the check engine light will flash. Turn off the ignition and wait 10 seconds, turn the ignition back to run and start the truck. If the check engine light is still illuminated repeat the previous steps again.

The Flash-Drive supplied with your tuner holds 1 stock file and 1 stock delete file if you need them use the instructional video located on the thumb drive that will walk you through this process to load these files.

YOU WILL NEED A WINDOWS BASED COMPUTER TO INSTALL THE EFI LIVE V8 SOFTWARE FROM www.efilive.com

If you have any questions, please contact us at: 423-815-5582 or send an e-mail to anarchydiesel@yahoo.com

UNDER THE HOOD-Please be sure to unplug the electrical connectors for the trucks EGR valve, EGR servo motor (on top of EGR cooler) and the AIR THROTTLE VALVE. All electrical connectors connecting to the exhaust must also be unplugged and the DPF removed. You can search for videos of these steps on any major search engine online.

*****REMINDER ALL SALES ARE FINAL AFTER INSTALLATION OF SOFTWARE ONTO THE VEHICLE. *****