

MM3 instructions

- 1. Plug the tuner into the OBD-II port under the dash as well as connecting the RT (3 pin) cable under the hood. The port for the RT cable is usually secured on the back side of the intake horn and has a dummy plug over the end.**
- 2. Create a stock file for the truck by doing the following:**
 1. Enter the main menu (...) button at the top center of the display.
 2. Next choose "ecm" and then "get stock file"
 3. The MM3 will write the stock file to the MicroSD card in the folder named "custom"
 4. Remove the MicroSD card from the tuner, and plug into a computer using the supplied USB adapter.
 5. Once the computer recognizes the sd card you will see a folder labeled "custom"
 6. Inside that folder will be a file named "STOCK.MM3". Copy that file onto the desktop of your computer and then attach it in an email to mm3tunes@gmail.com **along with the serial number below the bar code on the back of the tuner packaging.**
- 3. Once you have emailed your file to us we will respond with your custom tune files. Please allow 24 business hours for this to occur before contacting us. When you receive your file back do the following:**
 1. Plug the SD card into the computer using the supplied USB adapter.
 2. Download and save the attachments to your desktop or documents folder.
 3. You will have 2 file types on your desktop/documents. One will be an .ecm file. This file will need to be put in the "ECM" folder within the "CUSTOM" folder on the SD card.
 4. The other files (usually 4) will be .rtg files. These files need to go into the "RTG" folder also within the "CUSTOM" folder.
 5. Once you have the files in the appropriate folder install the SD card into the tuner and proceed to the next section.
- 4. Plug the MM3 into the truck if it is not already. Then navigate to the main menu (...) once again and select "ECM". Select "program custom file to ecm". Then select the file name that appears (should be stock_d.ecm). Then agree to the speed limiter setting and select Program. The tuner will now flash in the base file and unlock the ecm. This will take approximately 5-7 minutes.**
- 5. Once the download is complete start the truck. To change power levels on the fly, press the "RT" button on the top right of the tuner screen. This will take you to the menu where you will select "RT custom adder". Next you will select your power level (TOW, STREET,HOTSTREET,RACE). Once you have selected the desired power level the tuner will load**

the changes into the ecm on the fly (takes around 10-15 seconds). Once the update is complete the tuner will return to the gauges screen.

******* PLEASE SEE OTHER SIDE FOR SPECIAL NOTE ABOUT RT SETTINGS*******

The RT file must be re-loaded at every startup. In the "RT" menu section you can choose to send the RT file only once or at every startup. For most customers we suggest to set this to every startup. Then the tuner will then load the most recently selected RT file into the truck at each startup.